

Metal halide lamps for aquariums in various models. Various base designs; power levels (70 - 2 000 W). Special lamps; not suitable for general lighting purposes.

NEPTURION RX7s, Fc2/18, cable

* Double ended

* Special light spectrum

* Good colour rendering (10 000 K versions)

* For luminaires with protective glass

with a high colour temperature

* High colour stability for the entire service life

Article no.	Designation	Base	Ø [mm]	Length [mm]	LCL [mm]	Burning position	Ignition voltage [kV]	Lamp current [A]	Nominal lamp power [W]	Rated lamp power [W]	Nominal luminous flux [lm]	Rated luminous flux [lm]	Ambient temperature for max. luminous flux [°C]	Rated lamp efficiency [lm/W]	Mercury content [mg]	Colour temperature [K]	Colour temperature [descr.]	Colour rendering index Ra / Colour rendering level	Nominal service life [h]	Weighted energy consumption [kWh/1 000 h]	Energy efficiency class
220501	HIT-DE 70 10K RX7s	RX7s	20,0	114,2	-	p45	4	0,9	70	75,0	3 100	3 100	25°C	44,3	13,5	10 000	cool white	Ra80-89/1B	10 000	83	B
220504 ³⁾	HIT-DE 70 10K RX7s UVP	RX7s	20,0	114,2	-	p45	4	0,9	70	75,0	3 100	3 100	25°C	44,3	13,5	10 000	cool white	Ra80-89/1B	10 000	83	B
220104 ³⁾	HIT-DE 70 14K RX7s UVP	RX7s	20,0	114,2	-	p45	4	0,9	70	75,0	3 100	3 100	25°C	44,3	13,5	14 000	aqua white	n.a.	10 000	83	B
220001 ³⁾	HIT-DE 70 20K+ RX7s	RX7s	20,0	114,5	-	p45	4	0,9	70	75,0	1 700	1 700	25°C	24,3	18,0	20 000+	aqua blue	n.a.	10 000	83	C
221301	HIT-DE 150 10K RX7s	RX7s-24	23,0	132,0	-	p45	4	1,8	150	150,0	7 000	7 000	25°C	46,7	16,5	10 000	cool white	Ra>90/1A	10 000	165	B
221801	HIT-DE 150 14K RX7s	RX7s-24	23,0	132,0	-	p45	4	1,8	150	150,0	6 800	6 800	25°C	45,3	16,5	14 000	aqua white	n.a.	10 000	165	B
221001 ³⁾	HIT-DE 150 16K RX7s	RX7s-24	23,0	132,0	-	p45	4	1,8	150	150,0	6 600	6 600	25°C	44,0	49,5	16 000	aqua white	n.a.	10 000	165	B
221901 ¹⁾	HIT-DE 150 20K+ RX7s	RX7s-24	23,0	132,0	-	p45	4	1,8	150	150,0	3 000	3 000	25°C	20,0	18,0	20 000+	aqua blue	n.a.	10 000	165	C
222403 ³⁾	HIT-DE 250 10K Fc2/18	Fc2/18	25,0	139,0	-	p45	4	3	250	250,0	10 500	10 500	25°C	42,0	33,2	10 000	cool white	Ra80-89/1B	10 000	275	B
222603	HIT-DE 250 14K Fc2/18	Fc2/18	25,0	139,0	-	p45	4	3	250	250,0	10 600	10 600	25°C	42,4	35,0	14 000	aqua white	n.a.	6 000	275	B
222803 ³⁾	HIT-DE 250 16K Fc2/18	Fc2/18	25,0	139,0	-	p45	4	3	250	250,0	10 000	10 000	25°C	40,0	33,0	16 000	aqua white	n.a.	6 000	275	B
222703 ³⁾	HIT-DE 250 20K+ Fc2/18	Fc2/18	25,0	139,0	-	p45	4	3	250	250,0	5 000	5 000	25°C	20,0	30,0	20 000+	aqua blue	n.a.	6 000	275	C
131201	HIT-DE sa 2000 8K	Cable	40,0	187,0	-	p15	4	10,3	2 000	2 000	140 000	140 000	25°C	70,0	320,0	8 000	cool white	Ra80-89/1B	2 000	2200	A

1) On request; minimum order quantities may apply

3) Discontinued product; available as long as stock lasts