

SIGNION color RX7s / cable

* Double ended
* UV protection

* High colour saturation and constancy
* No extra colour filter needed in the luminaire

* Hot re-ignition possible
* For luminaires with protective glass

Article no.	Designation		Base	Ø [mm]	Length [mm]	LCL [mm]	Burning position	Ignition voltage [kV]	Lamp current [A]	Nominal lamp power [W]	Rated lamp power [W]	Nominal luminous flux [lm]	Rated luminous flux [lm]	Ambient temperature for max. luminous flux [°C]	Rated lamp efficiency [lm/W]	Mercury content [mg]	Assigned wavelength [nm]	Colour saturation [%]	Nominal service life [h]	Weighted energy consumption [kWh/1 000 h]	Energy efficiency class
224114	HIT-DE 70 gr RX7s	green	RX7s	20,0	114,2	-	p45	4	0,9	70	75,0	3 600	3 600	25°C	51,4	9,5	545	35	6 000	83	B
224124	HIT-DE 70 bl RX7	blue	RX7s	20,0	114,2	-	p45	4	0,9	70	75,0	1 700	1 700	25°C	24,3	18	475	60	6 000	83	C
224134	HIT-DE 70 mg RX7s	magenta	RX7s	20,0	114,2	-	p45	4	0,9	70	75,0	3 500	3 500	25°C	50,0	8,5	-500	18	6 000	83	B
224144 ³⁾	HIT-DE 70 or RX7s	orange	RX7s	20,0	114,2	-	p45	4	0,9	70	75,0	5 000	5 000	25°C	71,4	10	595	51	6 000	83	A
224311	HIT-DE 150 gr RX7s	green	RX7s-24	23,0	132,0	-	p45	4	1,8	150	150,0	9 500	9 500	25°C	63,3	18	530	50	6 000	165	A
224321	HIT-DE 150 bl RX7s	blue	RX7s-24	23,0	132,0	-	p45	4	1,8	150	150,0	3 000	3 000	25°C	20,0	18	465	56	6 000	165	C
224331	HIT-DE 150 mg RX7s	magenta	RX7s-24	23,0	132,0	-	p45	4	1,8	150	150,0	8 000	8 000	25°C	53,3	16	-515	33	6 000	165	B
224341 ³⁾	HIT-DE 150 or RX7s	orange	RX7s-24	23,0	132,0	-	p45	4	1,8	150	150,0	10 000	10 000	25°C	66,7	18	595	60	6 000	165	A
131213	HIT-DE la 2000 gr	green	Kabel	30,0	274,0	-	p15	4	10	2 000	2 000	200 000	200 000	25°C	100,0	240	530	45	6 000	2200	A+

1) On request; minimum order quantities may apply

3) Discontinued product; available as long as stock lasts