
FUGA 2 TRIANGLE SP

108 variants



Dimensions



Available colours

White **Black** **Grey**

FUGA 2 TRIANGLE SP is a suspended linear luminaire with an aluminium body and 600–1000 mm diameter. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space.

LUMINAIRE POWER

24 - 84.4 W

LUMINAIRE LUMINOUS FLUX

1,090 - 7,516 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FUGA 2 TRIANGLE SP.

Mounting position	**Pendant**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**Linear LED**
Control Gear	**Built-in ECG**
Ripple	**3**
Operating voltage	**230 V**
Power factor	**0.96**

Protection rating	**IP40 / IK04**
Insulation class	**Class I**
Lifetime	**>50.000h L70B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, CONVERSIONKIT+BATTERY**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 110° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 45.4 - 89.1 lm/W | Length 600 - 1,000 mm | Width 600 - 1,000 mm | Height 100 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	110°	24 - 84.4	**1,090 - 7,138**
940	4000 K	110°	24 - 84.4	**1,190 - 7,516**

Luminous flux range per version

Minimum 1,090 lm / 24 W / 930 / PRS0183CL001ON

Maximum 7,516 lm / 84.4 W / 940 / PRS0194CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >