NOTUS 16 UGR UP DOWN

270 variants



Dimensions



Available colours

White **Black** **Grey**

NOTUS 16 UGR UP DOWN is a suspended linear luminaire with an aluminium body and 54 mm width, 80 mm height, 590–4517 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. The profile family can create clean linear runs, with production up to 4500 mm per single profile where the version allows it and dedicated connectors for longer continuous compositions. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. The UP DOWN version combines direct and indirect light, also brightening the ceiling for a softer and more balanced atmosphere. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space. The standard colours white, black and grey have a textured finish.

LUMINAIRE POWER

21.3 - 170.7 W

LUMINAIRE LUMINOUS FLUX

2,239 - 18,999 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOTUS 16 UGR UP DOWN.

Mounting position	**Pendant**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**Linear LED**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**

Power factor	**0.96**
Protection rating	**IP40 / IK04**
Insulation class	**Class I**
Lifetime	**>100.000h L80B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, CONVERSIONKIT+BATTERY, TUBOCOVER**

Markings and catalogue references	**CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 73° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 104.9 - 111.5 lm/W | UGR longwise / parallel 15 - 16 / 16 | Length 590 - 4,517 mm | Width 54 mm | Height 80 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	73°	21.3 - 170.7	**2,239 - 17,911**
940	4000 K	73°	21.3 - 170.7	**2,375 - 18,999**

Luminous flux range per version

Minimum 2,239 lm / 21.3 W / 930 / PRS0375CL001ON

Maximum 18,999 lm / 170.7 W / 940 / PRS0404CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >