NOTUS 17 UP DOWN DAISY SP

540 variants



Dimensions



Available colours

White **Black** **Grey**

NOTUS 17 UP DOWN DAISY SP is a suspended linear luminaire with an aluminium body and 48 mm width, 104 mm height, 596–4488 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. The profile family can create clean linear runs, with production up to 4500 mm per single profile where the version allows it and dedicated connectors for longer continuous compositions. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. The UP DOWN version combines direct and indirect light, also brightening the ceiling for a softer and more balanced atmosphere. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space. The standard colours white, black and grey have a textured finish.

LUMINAIRE POWER

24 - 236.4 W

LUMINAIRE LUMINOUS FLUX

2,888 - 29,086 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOTUS 17 UP DOWN DAISY SP.

Mounting position	**Pendant**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**Linear LED**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**

Power factor	**0.96**
Protection rating	**IP20 / IK04**
Insulation class	**Class I**
Lifetime	**>80.000h L80B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Upwards & downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, CONVERSIONKIT+BATTERY**

Markings and catalogue references	**CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 96.8 - 124.1 lm/W | UGR longwise / parallel 11 - 12 / 16 | Length 596 - 4,488 mm | Width 48 mm | Height 104 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K		24 - 236.4	**2,888 - 27,582**
940	4000 K		24 - 236.4	**2,978 - 29,086**

Luminous flux range per version

Minimum 2,888 lm / 24 W / 930 / PRS1523CL001ON

Maximum 29,086 lm / 236.4 W / 940 / PRS1582CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >