COMIS 5 II SP

64 variants



Dimensions



Available colours

White **Black** **Grey** **Anodized grey**

COMIS 5 II SP is a suspended linear luminaire with integrated indirect LED lighting, with an aluminium body and 113 mm width, 79 mm height, 1000 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in matte white, matte black and anodized grey (grey is also available) finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length.

LUMINAIRE POWER

19.2 - 30 W

LUMINAIRE LUMINOUS FLUX

1,056 - 2,100 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS 5 II SP.

Mounting position	**Pendant**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP40 / IK05**
Body dimensions	**113 × 1000 × 79 mm**	Lifetime	**>50.000h L70B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Upwards & downwards**
Operating voltage	**230 V**	Accessories	**AUTO WIRE SUPPORT BLOCK**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 360° (VW) | Control On-Off, DALI2, DALI2 + Casambi | Light source Linear LED, LED Strip | Insulation class Class I, Class III

Luminous efficacy 55 - 70 lm/W | UGR longwise / parallel 12 - 14 / 13 - 16

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	360°	19.2 - 30	**1,056 - 1,650**
940	4000 K	360°	19.2 - 30	**1,344 - 2,100**

Luminous flux range per version

Minimum 1,056 lm / 19.2 W / 930 / PRS1917CL001ON

Maximum 2,100 lm / 30 W / 940 / PRS1920CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >