
COMIS 35 UP DOWN

48 variants



Dimensions



Available colours

White **Black** **Grey** **Anodized grey**

It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. The UP DOWN version combines direct and indirect light, also brightening the ceiling for a softer and more balanced atmosphere. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in matte white, matte black and anodized grey (grey is also available) finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space. Technical and photometric data refer to a 1 m length and an 18×35 mm section. The profile can be manufactured to the required length, up to 4.75 m. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length.

LUMINAIRE POWER

9.6 - 14.4 W

LUMINAIRE LUMINOUS FLUX

1,200 - 1,868 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS 35 UP DOWN.

Mounting position	**Pendant**	Operating voltage	**24 V**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**PMMA**	Protection rating	**IP20 / IK04**
Light source	**Linear LED**	Insulation class	**Class III**
Body dimensions	**18 × 1000 × 35 mm**	Lifetime	**>50.000h L70B10@35°C**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 360° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 124.9 - 135 lm/W | UGR longwise / parallel 14 - 18 / 15 - 19

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	360°	9.6 - 14.4	**1,200 - 1,798**
940	4000 K	360°	9.6 - 14.4	**1,296 - 1,868**

Luminous flux range per version

Minimum 1,200 lm / 9.6 W / 930 / PRS1921CL001ON

Maximum 1,868 lm / 14.4 W / 940 / PRS1924CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >