COMIS 40 FLEX

72 variants



Dimensions



Available colours

White **Black** **Grey** **Anodized grey**

COMIS 40 FLEX is a suspended linear luminaire with an aluminium body and 43.5 mm width, 44.5 mm height, 1000 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. It is available in matte white, matte black and anodized grey (grey is also available) finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length.

LUMINAIRE POWER

10 - 20 W

LUMINAIRE LUMINOUS FLUX

670 - 1,513 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS 40 FLEX.

Mounting position	**Pendant**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP40 / IK05**
Optic	**Silicone**	Insulation class	**Class III**
Light source	**Linear LED**	Lifetime	**>50.000h L70B10@35°C**
Body dimensions	**43.5 × 1000 × 44.5 mm**	Operating temperature	**-10…+45°C**
Control Gear	**Remote Electronic Driver**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Downwards**
Ripple	**3**	Accessories	**AUTO WIRE SUPPORT BLOCK**
Operating voltage	**24 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 67 - 75.7 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		10 - 20	**670 - 1,340**
930	3000 K		10 - 20	**699 - 1,398**
940	4000 K		10 - 20	**756 - 1,513**

Luminous flux range per version

Minimum 670 lm / 10 W / 927 / PRS1927CL001ON

Maximum 1,513 lm / 20 W / 940 / PRS1932CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >