COMIS RING OUT

96 variants



Dimensions



Available colours

White **Black** **Grey** **Anodized grey**

COMIS RING OUT is a suspended linear luminaire with an aluminium body and 12.8 mm width, 16.6 mm height, 600–1200 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. It is available in matte white, matte black and anodized grey (grey is also available) finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length.

LUMINAIRE POWER

23 - 45 W

LUMINAIRE LUMINOUS FLUX

1,610 - 3,377 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS RING OUT.

Mounting position	**Pendant**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**Linear LED**
Control Gear	**Remote Electronic Driver**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**
Power factor	**0.96**
Protection rating	**IP40 / IK05**
Insulation class	**Class I**
Lifetime	**>50.000h L70B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, DOUBLE SATIN COVER**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 119° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 70 - 75 lm/W | Length 600 - 1,200 mm | Width 12.9 mm | Height 16.6 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	119°	23 - 45	**1,610 - 3,151**
940	4000 K	119°	23 - 45	**1,725 - 3,377**

Luminous flux range per version

Minimum 1,610 lm / 23 W / 930 / PRS1933CL001ON

Maximum 3,377 lm / 45 W / 940 / PRS1940CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >