NOVUS OUT OPAL TAPE LED SP

144 variants



Dimensions



Available colours

White **Black** **Grey** **Anodized aluminium**

NOVUS OUT OPAL TAPE LED SP is a suspended linear luminaire with an aluminium body and 27 mm width, 55 mm height, 100–1000 mm reference length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. It is available in white, black and grey, as well as anodized aluminium finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space. Protection rating IP68.

LUMINAIRE POWER

1 - 15 W

LUMINAIRE LUMINOUS FLUX

55 - 1,050 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOVUS OUT OPAL TAPE LED SP.

Mounting position	**Pendant**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**Linear LED**
Control Gear	**Remote Electronic Driver**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**24 V**

Power factor	**0.96**
Protection rating	**IP68 / IK10**
Insulation class	**Class I**
Lifetime	**>50.000h L70B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, SKB 12, SKB 21, SKB**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 119° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 55 - 70.7 lm/W | UGR longwise / parallel 26 - 28 / 27 - 29 | Length 100 - 1,000 mm | Width 27 mm | Height 55 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	119°	1 - 15	**55 - 825**
940	4000 K	119°	1 - 15	**70 - 1,050**

Luminous flux range per version

Minimum 55 lm / 1 W / 930 / PRS1963CL001ON

Maximum 1,050 lm / 15 W / 940 / PRS1974CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >