# FUGA 2 HEXAGON

**96 variants**



## Dimensions




## Available colours

**White** **Black**

FUGA 2 HEXAGON is a surface-mounted linear luminaire with an aluminium body and 400–1000 mm diameter. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. It is available in white and black finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

**LUMINAIRE POWER**

11 - 121.9 W

**LUMINAIRE LUMINOUS FLUX**

499 - 10,857 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

**See all variants on bright.gr** >

# Technical characteristics

## Common data

Characteristics that apply to all versions of FUGA 2 HEXAGON.

| | | | |
|---|---|---|---|
| Mounting position | **Ceiling** | Power factor | **0.96** |
| Housing | **Aluminium** | Protection rating | **IP40 / IK04** |
| Optic | **PMMA** | Insulation class | **Class I** |
| Light source | **Linear LED** | Lifetime | **>50.000h L70B10@35°C** |
| Control Gear | **Built-in ECG** | Operating temperature | **-10…+45°C** |
| Colour uniformity | **3 SDCM** | Operating humidity | **5…95%** |
| Ripple | **3** | Lighting direction | **Downwards** |
| Operating voltage | **230 V** | Accessories | **CONVERSION KIT & BATTERY** |

**Markings and catalogue references** **CE • LM80 • LM79 • TM21 • REACH**

## Options per version

**Control On-Off, DALI2, DALI2 + Casambi**

Luminous efficacy 45.4 - 89.1 lm/W | Height 140 mm | Diameter 400 - 1,000 mm

| CRI/CCT | Colour temperature | Beams | Power (W) | Luminous flux (lm) |
|---|---|---|---|---|
| **930** | 3000 K | | 11 - 121.9 | **499 - 10,311** |
| **940** | 4000 K | | 11 - 121.9 | **546 - 10,857** |

### Luminous flux range per version

Minimum 499 lm / 11 W / 930 / PRC0001CL001ON

Maximum 10,857 lm / 121.9 W / 940 / PRC0016CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

**See all variants on bright.gr** >