FUGA 2 ROUND

144 variants



Dimensions



Ø600 | Ø800 | Ø1000 | Ø1200 | Ø1400 | Ø1600 | Ø1800 | Ø2000 |

Available colours

White **Black** **Grey**

FUGA 2 ROUND features a full circular luminous surface in 600, 800, 1000 and 1200 mm diameters. Available in white, black and grey, with On-Off, DALI2 and DALI2 with Casambi options. Suitable for architectural applications in commercial and residential spaces.

LUMINAIRE POWER

32 - 220 W

LUMINAIRE LUMINOUS FLUX

3,360 - 24,200 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FUGA 2 ROUND.

Mounting position	**Ceiling**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP40 / IK04**
Optic	**PMMA**	Insulation class	**Class I**
Light source	**Linear LED**	Lifetime	**>50.000h L70B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**
Operating voltage	**230 V**	Accessories	**CONVERSION KIT & BATTERY**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 110° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 105 - 110 lm/W | UGR longwise / parallel 19 - 23 / 19 - 23 | Height 100 mm | Diameter 600 - 1,200 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	110°	32 - 220	**3,360 - 23,100**
940	4000 K	110°	32 - 220	**3,520 - 24,200**

Luminous flux range per version

Minimum 3,360 lm / 32 W / 930 / PRC0061CL001ON

Maximum 24,200 lm / 220 W / 940 / PRC0076CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >