
# FUGA 2 SQUARE

**144 variants**



## Dimensions




## Available colours

White Black Grey

FUGA 2 SQUARE is a surface-mounted linear luminaire with an aluminium body and 450–1050 mm width, 140 mm height, 450–1050 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. Its anti-glare approach helps create a more comfortable lighting environment, especially in spaces where people spend longer periods of time. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

**LUMINAIRE POWER**

25 - 233.3 W

**LUMINAIRE LUMINOUS FLUX**

2,044 - 19,833 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

**See all variants on bright.gr >**

# Technical characteristics

## Common data

Characteristics that apply to all versions of FUGA 2 SQUARE.

| | | | |
|---|---|---|---|
| Mounting position | **Ceiling** | Power factor | **0.96** |
| Housing | **Aluminium** | Protection rating | **IP40 / IK04** |
| Optic | **PMMA** | Insulation class | **Class I** |
| Light source | **Linear LED** | Lifetime | **>50.000h L70B10@35°C** |
| Control Gear | **Built-in ECG** | Operating temperature | **-10…+45°C** |
| Colour uniformity | **3 SDCM** | Operating humidity | **5…95%** |
| Ripple | **3** | Lighting direction | **Downwards** |
| Operating voltage | **230 V** | Accessories | **CONVERSION KIT & BATTERY** |

**Markings and catalogue references** **CE • LM80 • LM79 • TM21 • REACH**

## Options per version

**Beams 110° (VW) | Control On-Off, DALI2, DALI2 + Casambi**

Luminous efficacy 80 - 86.9 lm/W | UGR longwise / parallel 20 - 25 / 20 - 24 | Length 450 - 1,050 mm | Width 450 - 1,050 mm | Height 140 mm

| CRI/CCT | Colour temperature | Beams | Power (W) | Luminous flux (lm) |
|---|---|---|---|---|
| **930** | 3000 K | 110° | 25 - 233.3 | **2,044 - 18,667** |
| **940** | 4000 K | 110° | 25 - 233.3 | **2,172 - 19,833** |

### Luminous flux range per version

Minimum 2,044 lm / 25 W / 930 / PRC0077CL001ON

Maximum 19,833 lm / 233.3 W / 940 / PRC0092CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

**See all variants on bright.gr** >