FUGA 2 TRIANGLE

108 variants



Dimensions



Available colours

White Black Grey

FUGA 2 TRIANGLE is a surface-mounted linear luminaire with an aluminium body and 140 mm height. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

24 - 84.4 W

LUMINAIRE LUMINOUS FLUX

1,090 - 7,516 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FUGA 2 TRIANGLE.

Mounting position	**Ceiling**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP40 / IK04**
Optic	**PMMA**	Insulation class	**Class I**
Light source	**Linear LED**	Lifetime	**>50.000h L70B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**
Operating voltage	**230 V**	Accessories	**CONVERSION KIT & BATTERY**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 110° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 45.4 - 89.1 lm/W | Length 600 - 1,000 mm | Height 140 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	110°	24 - 84.4	**1,090 - 7,138**
940	4000 K	110°	24 - 84.4	**1,190 - 7,516**

Luminous flux range per version

Minimum 1,090 lm / 24 W / 930 / PRC0093CL001ON

Maximum 7,516 lm / 84.4 W / 940 / PRC0104CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >