NOTUS 25

540 variants



Dimensions



Available colours

White **Black** **Grey**

The aluminium body is 46 mm wide and 64 mm high. Available lengths range from 585 to 4,536 mm. White, black and grey textured finishes and On-Off, DALI2 or Casambi controls are available depending on the product code.

LUMINAIRE POWER

11.3 - 135.1 W

LUMINAIRE LUMINOUS FLUX

857 - 10,853 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOTUS 25.

Mounting position	**Ceiling, Wall Mounted**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP54 / IK04**
Optic	**PMMA**	Insulation class	**Class I**
Light source	**Linear LED**	Lifetime	**>80.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**
Operating voltage	**230 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 105° (VW) | Control On-Off, DALI2, DALI2 + Casambi | Accessories AUTO WIRE SUPPORT BLOCK, CONVERSIONKIT+BATTERY, CONVERSION KIT + BATTERY

Luminous efficacy 75.5 - 80.4 lm/W | UGR longwise / parallel 24 - 26 / 24 - 26 | Length 585 - 4,536 mm | Width 46 mm | Height 64 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	105°	11.3 - 135.1	**857 - 10,282**
940	4000 K	105°	11.3 - 135.1	**908 - 10,853**

Luminous flux range per version

Minimum 857 lm / 11.3 W / 930 / PRC0105CL001ON

Maximum 10,853 lm / 135.1 W / 940 / PRC0164CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >