NOTUS 25 DAISY

540 variants



Dimensions



Available colours

White **Black** **Grey**

NOTUS 25 DAISY is a surface-mounted linear luminaire with an aluminium body and 46 mm width, 71 mm height, 566–4486 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. Among the available options, the asymmetric distribution directs light to one side, helping with walls, circulation areas, shelving or layouts where the light needs to work off-axis. The symmetrical version has an 80° beam. The profile family can create clean linear runs, with production up to 4500 mm per single profile where the version allows it and dedicated connectors for longer continuous compositions. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The standard colours white, black and grey have a textured finish.

LUMINAIRE POWER

12.7 - 101.3 W

LUMINAIRE LUMINOUS FLUX

1,557 - 15,372 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOTUS 25 DAISY.

Mounting position	**Ceiling**
Housing	**Aluminium**
Light source	**Linear LED**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**
Power factor	**0.96**

Protection rating	**IP40 / IK04**
Insulation class	**Class I**
Lifetime	**>80.000h L80B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, CONVERSIONKIT+BATTERY**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 53° (ASY), 80° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 122.6 - 151.9 lm/W | UGR longwise / parallel 15 / 15 | Length 566 - 4,486 mm | Width 46 mm | Height 71 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	53°, 80°	12.7 - 101.3	**1,557 - 14,652**
940	4000 K	53°, 80°	12.7 - 101.3	**1,634 - 15,372**

Luminous flux range per version

Minimum 1,557 lm / 12.7 W / 930 / PRC1629CL001ON

Maximum 15,372 lm / 101.3 W / 940 / PRC0194CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >