NOTUS 1 PL

72 variants



Dimensions



Available colours

White **Black** **Grey**

NOTUS 1 PL is a surface-mounted linear luminaire with an aluminium body and 1080–2535.7 mm width, 89 mm height, 1248–2928 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. The profile family can create clean linear runs, with production up to 4500 mm per single profile where the version allows it and dedicated connectors for longer continuous compositions. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The standard colours white, black and grey have a textured finish.

LUMINAIRE POWER

67.8 - 169.6 W

LUMINAIRE LUMINOUS FLUX

7,725 - 20,512 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOTUS 1 PL.

Mounting position	**Ceiling**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**Linear LED**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**

Power factor	**0.96**
Protection rating	**IP40 / IK04**
Insulation class	**Class I**
Lifetime	**>80.000h L80B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**CONVERSIONKIT+BATTERY, NOTUS 1 ANGULAR, SKB 12, SKB 21**

Markings and catalogue references	**CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 116° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 113.9 - 121 lm/W | Length 1,248 - 2,928 mm | Width 1,080 - 2,535.7 mm | Height 89 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	116°	67.8 - 169.6	**7,725 - 19,312**
940	4000 K	116°	67.8 - 169.6	**8,205 - 20,512**

Luminous flux range per version

Minimum 7,725 lm / 67.8 W / 930 / PRC1215CL001ON

Maximum 20,512 lm / 169.6 W / 940 / PRC1222CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >