PUTUS 4

12 variants



Dimensions



Available colours

White **Black**

PUTUS 4 is a surface-mounted linear luminaire with an integrated LED source, with an aluminium body and 37 mm width, 60 mm height, 1464 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. The integrated LED source with CRI90 supports good colour rendering, in 3000K and 4000K colour temperatures. It is available in white and black finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

25 W

LUMINAIRE LUMINOUS FLUX

3,250 - 3,500 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of PUTUS 4.

Mounting position	**Ceiling**	Colour uniformity	**3 SDCM**
Housing	**Aluminium**	Ripple	**3**
Optic	**Anti-Glare PC Shade**	Power factor	**0.96**
Light source	**SMD LED**	Protection rating	**IP20**
Body dimensions	**37 × 1464 × 60 mm**	Lighting direction	**Downwards**
Control Gear	**Built-in ECG**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 130 - 140 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K		25	**3,250**
940	4000 K		25	**3,500**

Luminous flux range per version

Minimum 3,250 lm / 25 W / 930 / PRC1477CL001ON

Maximum 3,500 lm / 25 W / 940 / PRC1478CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >