COMIS OUT LENS TAPE

144 variants



Dimensions



Available colours

White **Black** **Grey** **Anodized grey**

COMIS OUT LENS TAPE is a surface-mounted linear luminaire with an aluminium body and 17.5 mm width, 18 mm height, 100–1000 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. It is available in matte white, matte black and anodized grey (grey is also available) finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length.

LUMINAIRE POWER

1 - 14.4 W

LUMINAIRE LUMINOUS FLUX

91 - 1,512 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS OUT LENS TAPE.

Mounting position	**Ceiling**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP40 / IK05**
Optic	**Polycarbonate**	Insulation class	**Class III**
Light source	**Linear LED**	Lifetime	**>50.000h L70B10@35°C**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**
Operating voltage	**24 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 119° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 94.4 - 105.6 lm/W | UGR longwise / parallel 22 - 24 / 25 - 27 | Length 100 - 1,000 mm | Width 17.5 mm | Height 18 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	119°	1 - 14.4	**91 - 1,368**
940	4000 K	119°	1 - 14.4	**101 - 1,512**

Luminous flux range per version

Minimum 91 lm / 1 W / 930 / PRC1515CL001ON

Maximum 1,512 lm / 14.4 W / 940 / PRC1526CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >