COMIS 10 OUT

144 variants



Dimensions



Available colours

White **Black** **Grey** **Anodized grey**

COMIS 10 OUT is a surface-mounted linear luminaire with an aluminium body and 28 mm width, 16 mm height, 100–1000 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. It is available in matte white, matte black and anodized grey (grey is also available) finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length.

LUMINAIRE POWER

2 - 30 W

LUMINAIRE LUMINOUS FLUX

110 - 2,100 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS 10 OUT.

Mounting position	**Ceiling**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**Linear LED**
Control Gear	**Remote Electronic Driver**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**24 V**

Power factor	**0.96**
Protection rating	**IP40 / IK05**
Insulation class	**Class III**
Lifetime	**>50.000h L70B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, DOUBLE SATIN COVER**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 119° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 55 - 70.3 lm/W | UGR longwise / parallel 26 - 28 / 27 - 29 | Length 100 - 1,000 mm | Width 28 mm | Height 16 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	119°	2 - 30	**110 - 1,650**
940	4000 K	119°	2 - 30	**140 - 2,100**

Luminous flux range per version

Minimum 110 lm / 2 W / 930 / PRC1527CL001ON

Maximum 2,100 lm / 30 W / 940 / PRC1538CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >