
FUGA 2 SQUARE TRIMLESS A

144 variants



Dimensions



Available colours

White Black Grey

FUGA 2 SQUARE TRIMLESS A is a recessed linear luminaire with an aluminium body and 100 mm height. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. In recessed installations, the feed can be organised inside the false ceiling or installation void, keeping the final ceiling line clean. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention. Available with 9.6 or 15 W/m LED strips.

LUMINAIRE POWER

24 - 218.8 W

LUMINAIRE LUMINOUS FLUX

968 - 17,010 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FUGA 2 SQUARE TRIMLESS A.

Mounting position	**Ceiling Recessed**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**Linear LED**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**

Power factor	**0.96**
Protection rating	**IP40 / IK04**
Insulation class	**Class I**
Lifetime	**>50.000h L70B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, CONVERSIONKIT+BATTERY**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 110° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 40.3 - 77.8 lm/W | Length 450 - 1,050 mm | Width 450 - 1,050 mm | Height 100 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	110°	24 - 218.8	**968 - 16,170**
940	4000 K	110°	24 - 218.8	**1,054 - 17,010**

Luminous flux range per version

Minimum 968 lm / 24 W / 930 / PRT0001CL001ON

Maximum 17,010 lm / 218.8 W / 940 / PRT0016CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >