
NOTUS 25 DAISY TRIMLESS A

540 variants



Dimensions



Available colours

White **Black** **Grey**

NOTUS 25 DAISY TRIMLESS A is a recessed linear luminaire with an aluminium body and 46 mm width, 72 mm height, 566–4486 mm length. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. Among the available options, the asymmetric distribution directs light to one side, helping with walls, circulation areas, shelving or layouts where the light needs to work off-axis. The symmetrical version has an 80° beam. The profile family can create clean linear runs, with production up to 4500 mm per single profile where the version allows it and dedicated connectors for longer continuous compositions. In recessed installations, the feed can be organised inside the false ceiling or installation void, keeping the final ceiling line clean. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention. The standard colours white, black and grey have a textured finish.

LUMINAIRE POWER

12.7 - 101.3 W

LUMINAIRE LUMINOUS FLUX

1,557 - 13,066 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOTUS 25 DAISY TRIMLESS A.

Mounting position	**Ceiling Recessed**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP20 / IK04**
Optic	**Anti-Glare PC Shade**	Insulation class	**Class I**
Light source	**Linear LED**	Lifetime	**>80.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**
Operating voltage	**230 V**	Accessories	**CONVERSIONKIT+BATTERY**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 53° (ASY), 80° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 122.6 - 129.1 lm/W | UGR longwise / parallel 15 / 15 | Length 566 - 4,486 mm | Width 46 mm | Height 72 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	53°, 80°	12.7 - 101.3	**1,557 - 12,454**
940	4000 K	53°, 80°	12.7 - 101.3	**1,634 - 13,066**

Luminous flux range per version

Minimum 1,557 lm / 12.7 W / 930 / PRT0137CL001ON

Maximum 13,066 lm / 101.3 W / 940 / PRT0166CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >