NOTUS 19 SURFACE

144 variants



Dimensions



Available colours

White **Black** **Grey**

NOTUS 19 SURFACE is a linear wall luminaire with an aluminium body and 38 mm width, 82 mm height, 300–1155 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. The profile family can create clean linear runs, with production up to 4500 mm per single profile where the version allows it and dedicated connectors for longer continuous compositions. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. On the wall, it works as a lighting element that adds depth, texture or emphasis without requiring an intense luminous presence. The standard colours white, black and grey have a textured finish.

LUMINAIRE POWER

5.7 - 33.8 W

LUMINAIRE LUMINOUS FLUX

429 - 2,713 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOTUS 19 SURFACE.

Mounting position	**Ceiling**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP40 / IK04**
Optic	**PMMA**	Insulation class	**Class I**
Light source	**Linear LED**	Lifetime	**>80.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**
Operating voltage	**230 V**	Accessories	**CONVERSIONKIT+BATTERY**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 104° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 75.5 - 80.4 lm/W | UGR longwise / parallel 25 - 26 / 25 - 27 | Length 300 - 1,155 mm | Width 38 mm | Height 82 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	104°	5.7 - 33.8	**429 - 2,570**
940	4000 K	104°	5.7 - 33.8	**454 - 2,713**

Luminous flux range per version

Minimum 429 lm / 5.7 W / 930 / PRC1613CL001ON

Maximum 2,713 lm / 33.8 W / 940 / PRC1628CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >