
COMIS LINE

48 variants



Dimensions



Available colours

White **Black** **Grey** **Anodized grey**

Wall-mounted linear LED strip luminaire. Technical data refer to a 1 m length, with a 16.6×30 mm section and 9.6 or 15 W/m strip options, in 3000K or 4000K. The profile can be cut to the required length, up to 4.75 m. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length. Available in matte white, matte black and anodized grey (grey is also available).

LUMINAIRE POWER

9.6 - 15 W

LUMINAIRE LUMINOUS FLUX

475 - 945 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS LINE.

Mounting position	**Ceiling, Wall Mounted**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP40 / IK05**
Light source	**Linear LED**	Insulation class	**Class III**
Body dimensions	**16.6 × 1000 × 30 mm**	Lifetime	**>50.000h L70B10@35°C**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Operating voltage	**24 V**	Lighting direction	**Downwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 49.5 - 63 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K		9.6 - 15	**475 - 743**
940	4000 K		9.6 - 15	**605 - 945**

Luminous flux range per version

Minimum 475 lm / 9.6 W / 930 / PRW0241CL001ON

Maximum 945 lm / 15 W / 940 / PRW0262CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >