SEDO STATUR SMALL

210 variants



Dimensions



Available colours

Black | **Hillswick (EJ190)** | **Fair Isle (EJ186)** | **Maree (EJ195)** | **Inverness (EJ175)** | **Galilee (EJ125)** | **Pitlochry (EJ076)**

SEDO STATUR SMALL is a suspended linear luminaire with an integrated LED source, with a acoustic frame and 800 mm diameter, 1–3 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. The integrated LED source with CRI90 supports good colour rendering, with 16.2–26.3W versions, in 3000K and 4000K colour temperatures. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space.

LUMINAIRE POWER

16.2 - 26.3 W

LUMINAIRE LUMINOUS FLUX

1,713 - 2,677 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SEDO STATUR SMALL.

Mounting position	**Pendant**	Operating voltage	**36.2 V**
Housing	**Acoustic Panel**	Power factor	**0.96**
Optic	**PMMA**	Protection rating	**IP54 / IK04**
Light source	**SMD LED**	Insulation class	**Class III**
Body dimensions	**Ø 800 × 50 mm**	Lifetime	**>50.000h L80B10@35°C**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 118° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 97.3 - 113 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	118°	16.2 - 26.3	**1,713 - 2,560**
940	4000 K	118°	16.2 - 26.3	**1,830 - 2,677**

Luminous flux range per version

Minimum 1,713 lm / 16.2 W / 930 / PRA0121CL002ON

Maximum 2,677 lm / 26.3 W / 940 / PRA0130CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >