FUGA 2 RING SEDO SP

672 variants



Dimensions



Available colours

Black

Hillswick (EJ190)

Fair Isle (EJ186)

Maree (EJ195)

Inverness (EJ175)

Galilee (EJ125)

Pitlochry (EJ076)

FUGA 2 RING SEDO SP is a suspended linear luminaire with a acoustic frame and 600–2000 mm diameter, 600–2000 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space.

LUMINAIRE POWER

35.5 - 186.6 W

LUMINAIRE LUMINOUS FLUX

2,840 - 17,914 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FUGA 2 RING SEDO SP.

Mounting position	**Pendant**
Housing	**Acoustic Panel**
Optic	**PMMA**
Light source	**Linear LED**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**

Power factor	**0.96**
Protection rating	**IP40 / IK04**
Insulation class	**Class I**
Lifetime	**>80.000h L80B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, CONVERSIONKIT+BATTERY**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 110° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 80 - 96 lm/W | UGR longwise / parallel 17 - 22 / 17 - 22 | Length 600 - 2,000 mm | Height 200 mm | Diameter 600 - 2,000 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	110°	35.5 - 186.6	**2,840 - 16,048**
940	4000 K	110°	35.5 - 186.6	**3,195 - 17,914**

Luminous flux range per version

Minimum 2,840 lm / 35.5 W / 930 / PRA0131CL002ON

Maximum 17,914 lm / 186.6 W / 940 / PRA0162CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >