SEDO 2 NOTUS 16

1,260 variants



Dimensions



Available colours

Black | **Hillswick (EJ190)** | **Fair Isle (EJ186)** | **Maree (EJ195)** | **Inverness (EJ175)** | **Galilee (EJ125)** | **Pitlochry (EJ076)**

SEDO 2 NOTUS 16 is a suspended linear luminaire with a acoustic frame and 74 mm width, 200 mm height, 600–4520 mm length. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. The profile family can create clean linear runs, with production up to 4500 mm per single profile where the version allows it and dedicated connectors for longer continuous compositions. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space. The standard colours white, black and grey have a textured finish.

LUMINAIRE POWER

11.3 - 135.1 W

LUMINAIRE LUMINOUS FLUX

1,017 - 12,835 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SEDO 2 NOTUS 16.

Mounting position	**Pendant**
Housing	**Acoustic Panel**
Optic	**PMMA**
Light source	**Linear LED**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**

Power factor	**0.96**
Protection rating	**IP40 / IK04**
Insulation class	**Class I**
Lifetime	**>80.000h L80B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, CONVERSIONKIT+BATTERY, BASE DZ, TUBO COVER**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 104° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 90 - 95 lm/W | UGR longwise / parallel 24 - 26 / 24 - 26 | Length 600 - 4,520 mm | Width 74 mm | Height 200 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	104°	11.3 - 135.1	**1,017 - 12,159**
940	4000 K	104°	11.3 - 135.1	**1,074 - 12,835**

Luminous flux range per version

Minimum 1,017 lm / 11.3 W / 930 / PRA0315CL002ON

Maximum 12,835 lm / 135.1 W / 940 / PRA0374CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >