
SEDO BENE 20

324 variants



Dimensions



Available colours

Lagoon (4014)	Jungle (4012)	Cloud (4006)	Volcano (4002)

SEDO BENE 20 is a suspended linear luminaire with a acoustic frame and 1200 mm diameter. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. The deep anti-glare optical system reduces the visibility of the light source and helps keep the light comfortable in everyday use. The 15°–45° beam range allows the product to cover both focused accent lighting and wider illumination. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space.

LUMINAIRE POWER

8.8 - 17.6 W

LUMINAIRE LUMINOUS FLUX

776 - 1,652 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SEDO BENE 20.

Mounting position	**Pendant**	Ripple	**3**
Housing	**Acoustic Panel**	Power factor	**0.96**
Optic	**PMMA**	Protection rating	**IP20 / IK04**
Light source	**Linear LED**	Operating temperature	**-10…+45°C**
Body dimensions	**Ø 1200 × 10 mm**	Operating humidity	**5…95%**
Control Gear	**Remote Electronic Driver**	Lighting direction	**Downwards**
Colour uniformity	**3 SDCM**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 15° (N), 30° (M), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 82.5 - 100.5 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	15°, 30°, 45°	8.8 - 17.6	**776 - 1,452**
930	3000 K	15°, 30°, 45°	8.8 - 17.6	**836 - 1,560**
940	4000 K	15°, 30°, 45°	8.8 - 17.6	**880 - 1,652**

Luminous flux range per version

Minimum 776 lm / 8.8 W / 927 / PRA0468CL017ON

Maximum 1,652 lm / 17.6 W / 940 / PRA0488CL017ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >