FIGO SP UP DOWN

24 variants



Dimensions



Available colours

White **Black**

FIGO SP UP DOWN is a decorative pendant luminaire with an aluminium body. It suits dining tables, living areas, reception spaces, restaurants and hotels where the luminaire plays an important role in the appearance of the space. It is available in white and black finishes, with special RAL colours available on request for project-specific schemes. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space.

LUMINAIRE POWER

40 - 60 W

LUMINAIRE LUMINOUS FLUX

2,960 - 5,040 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FIGO SP UP DOWN.

Mounting position	**Pendant**	Ripple	**3**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**Microprismatic**	Operating temperature	**-10…+45°C**
Light source	**COB LED**	Operating humidity	**5…95%**
Control Gear	**Built-in ECG**	Lighting direction	**Upwards & downwards**
Colour uniformity	**3 SDCM**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 93° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 74 - 84 lm/W | Length 40 - 60 mm | Height 50 mm | Diameter 400 - 600 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	93°	40 - 60	**2,960 - 4,800**
940	4000 K	93°	40 - 60	**3,136 - 5,040**

Luminous flux range per version

Minimum 2,960 lm / 40 W / 930 / DES0045CL001ON

Maximum 5,040 lm / 60 W / 940 / DES0048CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >