
VISO 4 SP

72 variants



Dimensions



Available colours

White **Black** **Grey** **Brass-00**

VISO 4 SP is a decorative pendant luminaire with a metal body. It suits dining tables, living areas, reception spaces, restaurants and hotels where the luminaire plays an important role in the appearance of the space. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space.

LUMINAIRE POWER

1.1 - 1.7 W

LUMINAIRE LUMINOUS FLUX

115 - 176 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of VISO 4 SP.

Mounting position	**Pendant**	Power factor	**0.96**
Housing	**Metal**	Protection rating	**IP40 / IK07**
Light source	**H.P. LED**	Insulation class	**Class I**
Body dimensions	**Ø 50 × 75 mm**	Lifetime	**>60.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Wide spread**
Operating voltage	**230 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 360° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 94.1 - 119.1 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	360°	1.1 - 1.7	**115 - 160**
930	3000 K	360°	1.1 - 1.7	**119 - 164**
940	4000 K	360°	1.1 - 1.7	**131 - 176**

Luminous flux range per version

Minimum 115 lm / 1.1 W / 927 / DES0298CL002ON

Maximum 176 lm / 1.7 W / 940 / DES0303CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >