COMIS 14 DOWN

36 variants



Dimensions



Available colours

White **Black** **Grey** **Anodized grey**

COMIS 14 DOWN is a suspended linear luminaire with an aluminium body. It is 1000 mm long, with a 14 × 38 mm profile cross-section. It provides direct downward lighting. It is available in 2700 K, 3000 K and 4000 K, in matte white, matte black and anodized grey (grey is also available), with On-Off, DALI2 and Casambi control options. It is suitable for offices, retail spaces, hospitality and homes, above tables, worktops or as part of architectural compositions. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length.

LUMINAIRE POWER

10.5 W

LUMINAIRE LUMINOUS FLUX

473 - 542 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS 14 DOWN.

Mounting position	**Pendant**	Operating voltage	**230 V**
Housing	**Aluminium**	Power factor	**0.96**
Light source	**Linear LED**	Protection rating	**IP65 / IK05**
Body dimensions	**14 × 1000 × 38 mm**	Operating temperature	**-10…+45°C**
Control Gear	**Remote Electronic Driver**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Downwards**
Ripple	**3**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 110° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 45.1 - 51.6 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	110°	10.5	**473**
930	3000 K	110°	10.5	**521**
940	4000 K	110°	10.5	**542**

Luminous flux range per version

Minimum 473 lm / 10.5 W / 927 / PRS1984CL001ON

Maximum 542 lm / 10.5 W / 940 / PRS1986CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >