COMIS 14 RING UP DOWN

144 variants



Dimensions



Available colours

White **Black** **Grey** **Anodized grey**

COMIS 14 RING UP DOWN is a suspended circular luminaire with an aluminium body. It is available in 400, 1000, 1500 and 2000 mm diameters, with a 14 × 38 mm profile cross-section. It combines direct downward lighting with indirect upward lighting. It is available in 2700 K, 3000 K and 4000 K, in matte white, matte black and anodized grey (grey is also available), with On-Off, DALI2 and Casambi control options. It is suitable for offices, retail spaces, hospitality and homes, above tables, worktops or as part of architectural compositions. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length.

LUMINAIRE POWER

26.4 - 132 W

LUMINAIRE LUMINOUS FLUX

1,189 - 6,811 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS 14 RING UP DOWN.

Mounting position	**Pendant**	Operating voltage	**230 V**
Housing	**Aluminium**	Power factor	**0.96**
Light source	**Linear LED**	Protection rating	**IP65 / IK05**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Upwards & downwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 360° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 45.1 - 51.6 lm/W | Height 38 mm | Diameter 400 - 2,000 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	360°	26.4 - 132	**1,189 - 5,944**
930	3000 K	360°	26.4 - 132	**1,309 - 6,547**
940	4000 K	360°	26.4 - 132	**1,362 - 6,811**

Luminous flux range per version

Minimum 1,189 lm / 26.4 W / 927 / PRS1990CL001ON

Maximum 6,811 lm / 132 W / 940 / PRS2013CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >