TALIS 3 TABLE

72 variants



Dimensions



Available colours

White | Black | Grey | Gold | Copper | Nickel

TALIS 3 TABLE is a table lamp with an aluminium body. It is suitable for bedside tables, desks, consoles, hospitality spaces and places that need more personal or atmospheric lighting. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes.

LUMINAIRE POWER

4.4 - 8.9 W

LUMINAIRE LUMINOUS FLUX

164 - 232 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of TALIS 3 TABLE.

Mounting position	**Table Lights**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP40 / IK04**
Optic	**Plastic**	Insulation class	**Class II**
Light source	**H.P. LED**	Lifetime	**>50.000h L80B10@35°C**
Body dimensions	**Ø 200 × 305 mm**	Operating temperature	**-10…+45ºC**
Control Gear	**Remote Electronic Driver**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Downwards**
Ripple	**3**	Accessories	**COLORED CABLES**
Operating voltage	**230 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 117° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 24 - 41.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	117°	4.4 - 8.9	**164 - 214**
940	4000 K	117°	4.4 - 8.9	**182 - 232**

Luminous flux range per version

Minimum 164 lm / 4.4 W / 930 / DET0063CL004ON

Maximum 232 lm / 8.9 W / 940 / DET0066CL004ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >