
REDONO

16 variants



Dimensions



Available colours

White | Black | Grey | Red | Green | Blue | Beige | Yellow

REDONO is a floor lamp with an integrated LED source, with a metal body. It suits living rooms, hotels, reading corners and spaces where the luminaire needs to add both functional light and decorative presence. The integrated LED source with CRI90 supports good colour rendering, in 3000K and 4000K colour temperatures. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes.

LUMINAIRE POWER

21 W

LUMINAIRE LUMINOUS FLUX

1,775 - 1,885 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of REDONO.

Mounting position	**Floor**	Power factor	**0.96**
Housing	**Metal**	Protection rating	**IP20 / IK04**
Light source	**SMD LED**	Insulation class	**Class II**
Body dimensions	**Ø 345 × 1745 mm**	Lifetime	**>50.000h L80B10@35°C**
Colour uniformity	**3 SDCM**	Operating temperature	**-10…+45ºC**
Ripple	**3**	Operating humidity	**5…95%**
Operating voltage	**230 V**	Lighting direction	**Upwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 118° (VW)

Luminous efficacy 84.5 - 89.8 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	118°	21	**1,775**
940	4000 K	118°	21	**1,885**

Luminous flux range per version

Minimum 1,775 lm / 21 W / 930 / DEF0007CL001

Maximum 1,885 lm / 21 W / 940 / DEF0008CL001

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >