LATER

126 variants



Dimensions



Available colours

White | Black | Grey | Gold | Copper | Chrome | Nickel

LATER is a decorative wall light with integrated indirect LED lighting, with a metal body. It is used in homes, hotels, corridors, living areas and reception spaces where the luminaire also contributes to the atmosphere. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. On the wall, it works as a lighting element that adds depth, texture or emphasis without requiring an intense luminous presence.

LUMINAIRE POWER

3.2 - 12.8 W

LUMINAIRE LUMINOUS FLUX

49 - 262 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of LATER.

Mounting position	**Wall Mounted**	Power factor	**0.96**
Housing	**Metal**	Protection rating	**IP20 / IK05**
Light source	**LED Strip**	Insulation class	**Class I**
Control Gear	**Built-in ECG**	Lifetime	**>50.000h L70B10@35°C**
Colour uniformity	**3 SDCM**	Operating temperature	**-10…+45ºC**
Ripple	**3**	Operating humidity	**5…95%**
Operating voltage	**230 V**	Lighting direction	**Wide spread**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 180° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 15.2 - 20.9 lm/W | Length 3 - 12 mm | Height 45 mm | Diameter 183 - 380 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	180°	3.2 - 12.8	**49 - 195**
940	4000 K	180°	3.2 - 12.8	**64 - 262**

Luminous flux range per version

Minimum 49 lm / 3.2 W / 930 / DEW0001CL004ON

Maximum 262 lm / 12.8 W / 940 / DEW0006CL004ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >