
LATER STONE CIRCLE

72 variants



Dimensions



Available colours

Touche **Storm Negro** **Iseo**

LATER STONE CIRCLE is a decorative wall light with integrated indirect LED lighting, with a stone-look surface. It is used in homes, hotels, corridors, living areas and reception spaces where the luminaire also contributes to the atmosphere. It is available in soft beige, dark anthracite and petrol blue finishes. On the wall, it works as a lighting element that adds depth, texture or emphasis without requiring an intense luminous presence.

LUMINAIRE POWER

3.2 - 12.8 W

LUMINAIRE LUMINOUS FLUX

49 - 262 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of LATER STONE CIRCLE.

Mounting position	**Wall Mounted**	Power factor	**0.96**
Housing	**Μέταλλο, Λίθος**	Protection rating	**IP20 / IK05**
Light source	**LED Strip**	Insulation class	**Class I**
Control Gear	**Built-in ECG**	Lifetime	**>50.000h L70B10@35°C**
Colour uniformity	**3 SDCM**	Operating temperature	**-10…+45ºC**
Ripple	**3**	Operating humidity	**5…95%**
Operating voltage	**230 V**	Lighting direction	**Wide spread**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 180° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 15.2 - 20.9 lm/W | Length 3 - 12 mm | Height 48 mm | Diameter 200 - 600 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	180°	3.2 - 12.8	**49 - 195**
940	4000 K	180°	3.2 - 12.8	**64 - 262**

Luminous flux range per version

Minimum 49 lm / 3.2 W / 930 / DEW0007CL129ON

Maximum 262 lm / 12.8 W / 940 / DEW0013CL129ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >