
COMIS 4

48 variants



Dimensions



Available colours

White **Black** **Grey** **Anodized grey**

COMIS 4 is a decorative wall light with integrated indirect LED lighting, with an aluminium body. It is used in homes, hotels, corridors, living areas and reception spaces where the luminaire also contributes to the atmosphere. It is available in matte white, matte black and anodized grey (grey is also available) finishes, with special RAL colours available on request for project-specific schemes. On the wall, it works as a lighting element that adds depth, texture or emphasis without requiring an intense luminous presence. The profile is available in lengths up to 4,750 mm and can be cut or formed to suit project requirements. Dimensions and photometric data for each listed variant refer to its corresponding reference length.

LUMINAIRE POWER

19.2 - 30 W

LUMINAIRE LUMINOUS FLUX

1,056 - 2,100 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of COMIS 4.

Mounting position	**Wall Mounted**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**LED Strip**
Body dimensions	**70 × 1000 × 29 mm**
Control Gear	**Remote Electronic Driver**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**

Power factor	**0.96**
Protection rating	**IP40 / IK04**
Insulation class	**Class I**
Lifetime	**>50.000h L70B10@35°C**
Operating temperature	**-10…+45ºC**
Operating humidity	**5…95%**
Lighting direction	**Upwards & downwards**
Accessories	**DOUBLE SATIN COVER, LINEAR OPAL COVER, LENS SPOT COVER**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 360° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 55 - 70 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	360°	19.2 - 30	**1,056 - 1,650**
940	4000 K	360°	19.2 - 30	**1,344 - 2,100**

Luminous flux range per version

Minimum 1,056 lm / 19.2 W / 930 / DEW0068CL001ON

Maximum 2,100 lm / 30 W / 940 / DEW0071CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >