
VISO WALL 5

36 variants



Dimensions



Available colours

Nickel **Colourless**

VISO WALL 5 is a decorative wall light with a metal body. It is used in homes, hotels, corridors, living areas and reception spaces where the luminaire also contributes to the atmosphere. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. On the wall, it works as a lighting element that adds depth, texture or emphasis without requiring an intense luminous presence.

LUMINAIRE POWER

1.1 - 1.7 W

LUMINAIRE LUMINOUS FLUX

115 - 176 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of VISO WALL 5.

Mounting position	**Wall Mounted**	Power factor	**0.96**
Housing	**Metal**	Protection rating	**IP40 / IK07**
Light source	**H.P. LED**	Insulation class	**Class I**
Body dimensions	**Ø 20 × 290 mm**	Lifetime	**>50.000h L80B10@35°C**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45ºC**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Wide spread**
Operating voltage	**230 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 360° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 94.1 - 119.1 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	360°	1.1 - 1.7	**115 - 160**
930	3000 K	360°	1.1 - 1.7	**119 - 164**
940	4000 K	360°	1.1 - 1.7	**131 - 176**

Luminous flux range per version

Minimum 115 lm / 1.1 W / 927 / DEW0091CL007ON

Maximum 176 lm / 1.7 W / 940 / DEW0096CL007ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >