

STIPO 3 H.P.LED

54 variants



Dimensions



Available colours

White **Black** **Grey**

STIPO 3 H.P.LED is a decorative wall light with an aluminium body. It is used in homes, hotels, corridors, living areas and reception spaces where the luminaire also contributes to the atmosphere. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. Recessed installation integrates the luminaire discreetly into the wall.

LUMINAIRE POWER

1.1 - 1.7 W

LUMINAIRE LUMINOUS FLUX

85 - 130 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of STIPO 3 H.P.LED.

Mounting position	**Recessed Wall Fitting**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP20 / IK05**
Light source	**H.P. LED**	Insulation class	**Class III**
Body dimensions	**50 × 50 × 35 mm**	Lifetime	**>50.000h L80B10@35°C**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45ºC**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**
Operating voltage	**3 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 50° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 69.4 - 88.2 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	50°	1.1 - 1.7	**85 - 118**
930	3000 K	50°	1.1 - 1.7	**88 - 121**
940	4000 K	50°	1.1 - 1.7	**97 - 130**

Luminous flux range per version

Minimum 85 lm / 1.1 W / 927 / DEW0127CL001ON

Maximum 130 lm / 1.7 W / 940 / DEW0132CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >