
RAVUS WALL 1

3 variants



Dimensions



Available colours

White

RAVUS WALL 1 is a decorative wall light with an aluminium body. It is used in homes, hotels, corridors, living areas and reception spaces where the luminaire also contributes to the atmosphere. Special RAL colours can be requested for projects with a specific colour scheme. On the wall, it works as a lighting element that adds depth, texture or emphasis without requiring an intense luminous presence.

LUMINAIRE POWER

6 W

LUMINAIRE LUMINOUS FLUX

450 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of RAVUS WALL 1.

Mounting position	**Wall Mounted**	Ripple	**3**
Housing	**Aluminium**	Operating voltage	**230 V**
Light source	**H.P. LED**	Power factor	**0.96**
Body dimensions	**153 × 183 × 185 mm**	Protection rating	**IP20**
Colour uniformity	**3 SDCM**	Lighting direction	**Sideways**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 25° (M), 40° (M), 60° (W)

Luminous efficacy 75 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	25°, 40°, 60°	6	**450**

Luminous flux range per version

Minimum 450 lm / 6 W / 930 / DEW0139CL001

Maximum 450 lm / 6 W / 930 / DEW0139CL001

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >