FERUS 20 IN SQ H.P.LED

432 variants



Dimensions



Available colours

White **Black** **Grey** **Chrome** **Nickel** **Titanium**

FERUS 20 IN SQ H.P.LED is a decorative wall light with a metal body. It is used in homes, hotels, corridors, living areas and reception spaces where the luminaire also contributes to the atmosphere. Depending on the project, the 8°–45° beams can be used for either more concentrated or more open lighting. The oval option 13x45° complements the range when the light needs to follow a shelf, counter, corridor or long architectural line. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention. The head has a 110 mm axial length and a 30×30 mm square section. The visible plate is 50×100 mm and the rear recessed section is 80×40 mm.

LUMINAIRE POWER

1.1 - 1.7 W

LUMINAIRE LUMINOUS FLUX

115 - 176 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FERUS 20 IN SQ H.P.LED.

Mounting position	**Wall Mounted**	Power factor	**0.96**
Housing	**Brass**	Protection rating	**IP40 / IK05**
Light source	**H.P. LED**	Insulation class	**Class I**
Body dimensions	**30 × 110 × 30 mm**	Lifetime	**>50.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45ºC**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**
Operating voltage	**230 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams (ASY), 8° (N), 25° (M), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 94.1 - 119.1 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	1.1 - 1.7	**115 - 160**
930	3000 K	8°, 25°, 45°	1.1 - 1.7	**119 - 164**
940	4000 K	8°, 25°, 45°	1.1 - 1.7	**131 - 176**

Luminous flux range per version

Minimum 115 lm / 1.1 W / 927 / DER0125CL001ON

Maximum 176 lm / 1.7 W / 940 / DER0130CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >