FERUS 60

432 variants



Dimensions



Available colours

White **Black** **Grey** **Chrome** **Nickel** **Titanium**

FERUS 60 is a decorative wall light with a metal body. It is used in homes, hotels, corridors, living areas and reception spaces where the luminaire also contributes to the atmosphere. The 8°–45° beam range offers different levels of light concentration. The additional oval distribution 13x45° spreads the beam further lengthwise, helping shelves, counters, corridors and applications with a long, narrow geometry. It is available in multiple finish options, with special RAL colours available on request for project-specific schemes. On the wall, it works as a lighting element that adds depth, texture or emphasis without requiring an intense luminous presence. Cylindrical head measuring 110 mm in axial length and 30 mm in diameter. The separate wall base is 170 mm high and 70 mm wide.

LUMINAIRE POWER

1.1 - 1.7 W

LUMINAIRE LUMINOUS FLUX

115 - 176 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FERUS 60.

Mounting position	**Wall Mounted**	Power factor	**0.96**
Housing	**Metal**	Protection rating	**IP40 / IK05**
Light source	**H.P. LED**	Insulation class	**Class I**
Body dimensions	**Ø 30 mm**	Lifetime	**>50.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45ºC**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**
Operating voltage	**230 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams (ASY), 8° (N), 25° (M), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 94.1 - 119.1 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	1.1 - 1.7	**115 - 160**
930	3000 K	8°, 25°, 45°	1.1 - 1.7	**119 - 164**
940	4000 K	8°, 25°, 45°	1.1 - 1.7	**131 - 176**

Luminous flux range per version

Minimum 115 lm / 1.1 W / 927 / DER0221CL001ON

Maximum 176 lm / 1.7 W / 940 / DER0226CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >