NUDO OUTDOOR H.P.LED

192 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

It is suitable for facades, entrances, gardens, paths and exterior points that need durable construction and controlled lighting presence. The standard 8°–45° beams allow a choice between narrower and wider lighting, depending on the application. Where coverage needs to extend along one axis, the oval 13x45° beam adds a useful option for elongated surfaces and circulation zones. It is available in white, black, grey and anthracite finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. On the wall, it works as a lighting element that adds depth, texture or emphasis without requiring an intense luminous presence. The head measures 215×140×95 mm. The 200 mm drawing dimension refers to the wall mounting projection.

LUMINAIRE POWER

26.6 - 40 W

LUMINAIRE LUMINOUS FLUX

2,534 - 6,000 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NUDO OUTDOOR H.P.LED.

Mounting position	**Ceiling, Wall Mounted, Floor**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP65 / IK07**
Optic	**Safety Glass Clear**	Insulation class	**Class I**
Light source	**H.P. LED**	Lifetime	**>50.000h L80B10@35°C**
Body dimensions	**140 × 215 × 95 mm**	Operating temperature	**-20…+45ºC**
Control Gear	**Built-in ECG**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Sideways**
Ripple	**3**	Accessories	**MOUNTING SET**
Operating voltage	**230 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams (ASY), 8° (UN), 25° (NM), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 95 - 150 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	8°, 25°, 45°	26.6 - 40	**2,534 - 5,800**
940	4000 K	8°, 25°, 45°	26.6 - 40	**2,660 - 6,000**

Luminous flux range per version

Minimum 2,534 lm / 26.6 W / 930 / PJ0117CL001ON

Maximum 6,000 lm / 40 W / 940 / PJ0116CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >