SATIS OUTDOOR H.P.LED

192 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

SATIS OUTDOOR H.P.LED is a outdoor projector with an aluminium body and 240 mm width, 95 mm height, 240 mm length. It is suitable for facades, entrances, gardens, paths and exterior points that need durable construction and controlled lighting presence. Beyond the 8°–45° beams, which cover different levels of concentration, the oval 13x45° beam is available for applications that need more reach in one direction. This allows the same product to support both classic directional lighting and more elongated coverage. It is available in white, grey, black and anthracite finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. On the wall, it works as a lighting element that adds depth, texture or emphasis without requiring an intense luminous presence.

LUMINAIRE POWER

26.6 - 40 W

LUMINAIRE LUMINOUS FLUX

3,215 - 4,660 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of SATIS OUTDOOR H.P.LED.

Mounting position	**Ceiling, Wall Mounted, Floor, Amenity**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP65 / IK05**
Optic	**Safety Glass Clear**	Insulation class	**Class I**
Light source	**H.P. LED**	Lifetime	**>60.000h L80B10@35°C**
Body dimensions	**240 × 240 × 95 mm**	Operating temperature	**-20…+45ºC**
Control Gear	**Built-in ECG**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Sideways**
Ripple	**3**	Accessories	**MOUNTING SET**
Operating voltage	**230 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams (ASY), 8° (UN), 25° (NM), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 109.8 - 130.3 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	8°, 25°, 45°	26.6 - 40	**3,215 - 4,390**
940	4000 K	8°, 25°, 45°	26.6 - 40	**3,467 - 4,660**

Luminous flux range per version

Minimum 3,215 lm / 26.6 W / 930 / PJ0179CL001ON

Maximum 4,660 lm / 40 W / 940 / PJ0182CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >