REGIO OUTDOOR H.P.LED

288 variants



Dimensions



Available colours

Anthracite

LUMINAIRE POWER

11.1 - 38.2 W

LUMINAIRE LUMINOUS FLUX

1,145 - 4,225 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of REGIO OUTDOOR H.P.LED.

Mounting position	**Ceiling, Wall Mounted, Floor, Amenity**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP65 / IK05**
Optic	**Safety Glass Clear**	Insulation class	**Class I**
Light source	**H.P. LED**	Lifetime	**>50.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-20…+45ºC**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**
Operating voltage	**230 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams (ASY), 8° (UN), 25° (NM), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 100 - 117.6 lm/W | Length 635 - 1,535 mm | Width 74 mm | Height 73 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	11.1 - 38.2	**1,145 - 3,841**
930	3000 K	8°, 25°, 45°	11.1 - 38.2	**1,185 - 3,937**
940	4000 K	8°, 25°, 45°	11.1 - 38.2	**1,305 - 4,225**

Luminous flux range per version

Minimum 1,145 lm / 11.1 W / 927 / FA0085CL009ON

Maximum 4,225 lm / 38.2 W / 940 / FA0108CL009ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >