DENUS GROUND INOX H.P.LED

72 variants



Dimensions



Available colours

Nickel

LUMINAIRE POWER

5.6 - 8.1 W

LUMINAIRE LUMINOUS FLUX

572 - 880 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of DENUS GROUND INOX H.P.LED.

Mounting position	**Floor**	Operating voltage	**230 V**
Housing	**Inox**	Power factor	**0.96**
Optic	**Safety Glass Clear**	Protection rating	**IP67 / IK05**
Light source	**H.P. LED**	Insulation class	**Class I**
Body dimensions	**87 × 370 × 68 mm**	Lifetime	**>60.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-30…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Upwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams (ASY), 8° (UN), 25° (NM), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 98.8 - 116.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	5.6 - 8.1	**572 - 800**
930	3000 K	8°, 25°, 45°	5.6 - 8.1	**592 - 820**
940	4000 K	8°, 25°, 45°	5.6 - 8.1	**652 - 880**

Luminous flux range per version

Minimum 572 lm / 5.6 W / 927 / GR0001CL007ON

Maximum 880 lm / 8.1 W / 940 / GR0006CL007ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >