
NOXA 2 OUT

220 variants



Dimensions



Available colours

White **Black** **Grey** **Anthracite**

LUMINAIRE POWER

1.1 - 4.8 W

LUMINAIRE LUMINOUS FLUX

85 - 390 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOXA 2 OUT.

Mounting position	**Wall Mounted**	Protection rating	**IP65 / IK08**
Housing	**Brass**	Insulation class	**Class I**
Optic	**Opal Polycarbonate**	Lifetime	**>50.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-20…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**
Operating voltage	**230 V**	Accessories	**MOUNTING SET**
Power factor	**0.96**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams (ASY) | Control On-Off, DALI2, DALI2 + Casambi | Light source H.P. LED, G9 LED Lamp

Luminous efficacy 73.8 - 88.2 lm/W | Length 102 - 190 mm | Width 102 - 170 mm | Height 55 - 57 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K		1.1 - 4.8	**85 - 354**
930	3000 K		1.1 - 4.8	**88 - 363**
940	4000 K		1.1 - 4.8	**97 - 390**

Luminous flux range per version

Minimum 85 lm / 1.1 W / 927 / WF0003CL001ON

Maximum 390 lm / 4.8 W / 940 / WF0020CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >