
RITUS 60 MOB IP65

48 variants



Dimensions



Available colours

White

RITUS 60 MOB IP65 features an integrated 6 W COB LED source with a final luminaire output of 600 lm. It is available in 2700, 3000, 3500 and 4000 K with 15°, 24°, 36° and 60° beam options. Each listed variant has a fixed colour temperature and beam angle. It is rated IP65 and uses a remote driver with the control options listed for each variant. IP65 protection for recessed ceiling installation.

LUMINAIRE POWER

6 W

LUMINAIRE LUMINOUS FLUX

600 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of RITUS 60 MOB IP65.

Mounting position	**Ceiling Recessed**	Operating voltage	**230 V**
Housing	**Aluminium**	Protection rating	**IP65 / IK04**
Light source	**COB LED**	Lighting direction	**Sideways**
Body dimensions	**Ø 73 × 71 mm**	Accessories	**HONEY COMB**
Control Gear	**Remote Electronic Driver**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 15° (UN), 24° (N), 36° (M), 60° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 100 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	15°, 24°, 36°, 60°	6	**600**
930	3000 K	15°, 24°, 36°, 60°	6	**600**
935	3500 K	15°, 24°, 36°, 60°	6	**600**
940	4000 K	15°, 24°, 36°, 60°	6	**600**

Luminous flux range per version

Minimum 600 lm / 6 W / 927 / DL5322CL001ON

Maximum 600 lm / 6 W / 927 / DL5322CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >