
TALIS 1 BRASS

90 variants



Dimensions



Available colours

White | Black | Grey | Anthracite | Colourless

LUMINAIRE POWER

5.5 - 8.2 W

LUMINAIRE LUMINOUS FLUX

311 - 477 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of TALIS 1 BRASS.

Mounting position	**Bollard**	Power factor	**0.96**
Housing	**Brass**	Protection rating	**IP65 / IK05**
Optic	**Opal Polycarbonate**	Insulation class	**Class I**
Light source	**H.P. LED**	Lifetime	**>50.000h L80B10@35°C**
Body dimensions	**Ø 140 × 650 mm**	Operating temperature	**-20…+45°C**
Control Gear	**Remote Electronic Driver**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Downwards**
Ripple	**3**	Accessories	**BRASS NAIL, CONNECTION TOOL 3**
Operating voltage	**230 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 117° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 52.7 - 64.7 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	117°	5.5 - 8.2	**311 - 432**
930	3000 K	117°	5.5 - 8.2	**322 - 443**
940	4000 K	117°	5.5 - 8.2	**356 - 477**

Luminous flux range per version

Minimum 311 lm / 5.5 W / 927 / BO0027CL001ON

Maximum 477 lm / 8.2 W / 940 / BO0032CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >