VISO 2

36 variants



Dimensions



Available colours

Nickel **Colourless**

LUMINAIRE POWER

1.1 - 1.7 W

LUMINAIRE LUMINOUS FLUX

115 - 176 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of VISO 2.

Mounting position	**Bollard**	Power factor	**0.96**
Housing	**Brass**	Protection rating	**IP65 / IK07**
Optic	**Lens**	Insulation class	**Class III**
Light source	**H.P. LED**	Lifetime	**>60.000h L80B10@35°C**
Body dimensions	**Ø 20 × 1175 mm**	Operating temperature	**-20…+45°C**
Control Gear	**Remote Electronic Driver**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Downwards**
Ripple	**3**	Accessories	**CONNECTION BOX**
Operating voltage	**3 V**		

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 360° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 94.1 - 119.1 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	360°	1.1 - 1.7	**115 - 160**
930	3000 K	360°	1.1 - 1.7	**119 - 164**
940	4000 K	360°	1.1 - 1.7	**131 - 176**

Luminous flux range per version

Minimum 115 lm / 1.1 W / 927 / BO0053CL109ON

Maximum 176 lm / 1.7 W / 940 / BO0058CL109ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >